

TWIN PEAKS LAMINATE

INSTALLATION INSTRUCTIONS

PLEASE READ ALL INSTRUCTIONS CAREFULLY BEFORE YOU BEGIN INSTALLATION. IMPROPER INSTALLATION WILL VOID WARRANTY

- Always check panels for defects such as chips and color or sheen differences under good light conditions. Also check that channel is clean and free of debris. For best color match when using panels from two or more packages, check to be sure all the patterns are the same. Be sure to use laminate out of more than one box to achieve proper pattern repeat.
- Your Laminate flooring **MUST** be allowed to acclimate to the environment of the installation area. Leave the closed packages in a horizontal position in the room for 48 hours prior to installation. Preferable temperature should be approximately 17-23°C (62-73°F) with a relative humidity of 45-60%. Humidity should never be allowed to drop below 30% as this may cause gapping.
- If existing baseboard moldings are difficult to remove, they may be left in place. Quarter round molding is all that is needed to cover the expansion space between flooring and baseboard.

TOOLS AND SUPPLIES REQUIRED ARE:

Spacers, tapping block, pull bar, saw, hammer, utility knife, pencil, tape measure, ruler and construction adhesive.

If you are installing over a crawlspace or on a concrete floor, you must also install a 4 mil (or thicker) polyethylene vapor barrier.


SUITABLE TYPES OR SUBFLOORS AND FLOOR PREPARATION

The underfloor or subfloor must be thoroughly even, dry, clean and solid. Carpet staples or glue residue must be removed and floor must be clean to ensure proper installation.

To check for evenness, hammer a nail into the center of the floor. Tie a string to the nail and push the knot against the floor. Pull the string tight to the farthest corner of the room and examine the floor at eye level for any gaps between the string and floor. Move the string around the perimeter of the room noting any gaps larger than 4.8mm (3/16"). Any floor unevenness of

- More than 4.8mm (3/16") per 3m (10ft) must be sanded down or filled in with appropriate filler.
- Floors must be carefully checked for moisture problems. Any moisture problems need to be solved before installation. New concrete needs to cure for at least 60 days before installation.

THIS PRODUCT IS NOT SUITABLE FOR DAMP ROOMS SUCH AS BATHROOMS, SAUNAS, AND ROOMS WITH DAMP CONCRETE, ROOMS WITH FLOOR DRAINS OR ROOMS THAT COULD POTENTIALLY FLOOD.



BASIC INSTALLATION

- For installation on concrete floors or any floors over a crawl space a vapor barrier MUST be laid down first. Use 4 mil poly. Run the poly 5cm (2") up walls and overlap seams 45cm (18"). Tape seams. **Diagram 1.**
- You will need to remove the tongue on the long side of the panels that face the wall, from the appropriate amount of panels for your first row. This is to ensure that the decorative surface of the laminate floor is well under the finished trim when installed. Use a utility knife to score through the tongue several times until it easily snaps off.
- Start in a corner by placing the first panel with its trimmed side facing the wall. Use spacers along each wall to maintain an expansion space of 8-12mm (5/16"-3/8") between the wall and the flooring. **Diagram 2.**

REMEMBER THAT THIS PRODUCT IS PRIMARILY WOOD AND NEEDS ROOM TO EXPAND AND CONTRACT. AT NO POINT SHOULD YOU ATTACH THE FLOOR TO ANY SURFACE.

- To attach your second panel, insert the end tongue of the panel into the end groove of the first panel at a 45 angle. Lower the panel flat to the floor. Lineup edges carefully. **Diagram 3.**
- Continue connecting the first row until you reach the last full panel. Fit the last panel by rotating the panel 180° with the pattern side upward, place beside row, mark and then saw off excess. Attach as described above. **Diagram 4.**
- When using a handsaw cut on the decorative surface. If you use a jig or circular saw cut with the decorative side down to avoid chipping. **Diagram 5.**
- Begin the next row with the off cut piece from the previous row to stagger the pattern. Pieces should be a minimum of 20cm (8") long and joint offset should be at least 40cm (16"). **Diagram 6.**
- To start your second row, tilt and push the side tongue of the panel into the side groove of the very first panel at about 30°. When lowered, the plank will click into place. **Diagram 7.**
- Attach the second panel of the new row on the long side. Tilt and push this panel as close as possible to the previous row at 30°. Make sure edges are lined up. Lower panel to the floor, locking the end tongue into the end groove of the first panel. Continue laying remaining panels in this manner. **Diagram 8/9.**

- To fit the last row, lay a panel on top of the previous row. With the tongue to the wall, lay another panel upside down on the one to be measured and use it as a ruler. Don't forget to allow room for spacers. Cut the panel and attach into position. **Diagram 10.**
- Door frames and heating vents also require expansion room. First cut the panel to the correct length. Then place the cut panel next to its actual position and use a ruler to measure the areas to be cut out and mark them. Cut out the marked points allowing the necessary expansion distance on each side. **Diagram 11.**
- You can trim door frames by turning a panel upside down and using a hand saw to cut away the necessary height so that panels slide easily underframes. **Diagram 12.**

FINISHING MOLDING

- Reducer molding is used to finish flooring when the adjoining surface is lower than the laminate flooring or when flooring meets carpet. Position the U track 7mm (1.4") between each edge of the flooring. Screw, nail or glue down the track directly to the subfloor and then insert the reducing strip into the track.
- T-molding is used to finish flooring when two level surfaces meet in doorway or for expansion joints. Install same as above. If your room is more than 7m (23') wide you will need to allow for an expansion joint. Expansion joints use T-molding and can be positioned in any inconspicuous place.
- Landing/stair molding is used to finish flooring on landings or stair edges. Moldings need to be glued and screwed down to the sub-floor for safety and stability. Color fill should be used to cover counter sunk screws.
- To finish the perimeter of the room install quarter round molding using finishing nails. Quarter Round molding is nailed directly into the baseboard.

MAINTENANCE AND CLEANING

- Preferable temperature should be approximately 17-23° C (62-73F) with a relative humidity of 45-60%. Humidity should never be allowed to drop below 30% as this may cause gapping.
- Do not use a wet spray micro fiber mop. Use a well rung out damp cloth to clean up any dirt and footprints but avoid using excessive moisture. All spills should be cleaned up immediately. Never use wax, polish or souring agents as they may dull or distort the finish.
- To avoid scratches apply felt pads to your furniture legs and use only soft rubber casters. Protect high traffic areas with runners and area rugs.
- It's a good idea to save a few boards in case of accidental damage. Boards can be replaced or repaired by a Flooring Professional.